

## MULTI-FUNCTIONS

- ✓ **12V battery** from 4 to 150 Ah
  - VRLA/GEL
  - AGM / SPIRAL / Water proof batteries
  - SLI (Opened liquid batteries)
- ✓ **12V starter**
- ✓ **12V alternator circuit**

## TESTING THE BATTERY

### Multi-standards

- SAE standard: 40 to 1200 CCA
- DIN standard: 20 to 670 CCA
- IEC standard: 25 to 790 CCA
- EN standard : 35 to 1125 CCA
- CA (MCA) standard: 70 to 1440 CCA

### Test

- Without disconnecting the battery from the vehicle
- Or on a separate battery

### Protection polarity reversal

### Instantaneous analysis with digital display on a bright LCD screen

- Battery voltage (from 4.5V to 16V)
- Battery health and charge state in %
- Its impedance
- The CCA according to the standard



## TESTING THE STARTER

- Test the starting voltage and indicate if the starter is in a good state or if it is necessary to check the connections.

## TESTING THE ALTERNATOR CIRCUIT

- Test the no-load and charging voltage.

## SES +

- ✓ 3 in 1 tester
- ✓ **Ultra compact** design
- ✓ Easy to use
- ✓ Display of **all the information** on a large LCD screen



REF. 055261 **DHC – BT280**

**POWER SUPPLY:** Draws power from the battery being tested. No internal batteries required

**TEMPERATURE CONDITION:** 0°C to 50°C

**CABLES:** 0.5 m

**SIZE:** 120 x 79 x 22,7 mm

**WEIGHT:** 218 g

## NOTES